



**NOTES**

- DESIGN PRESSURE 4.5MPA
- THE MINIMUM BURST PRESSURE OF THE PRODUCT IS THREE TIMES THE DESIGN PRESSURE
- DIAGONAL DIFFERENCE MAX 7mm
- TOLERANCE IF NOT SPECIFIED SHALL COMPLY WITH STANDARD ISO 2768-1 CLASS C(GB/T 1804 CLASS C)
- SEAL 0.01~0.05MPA NITROGEN GAS IN THE PRODUCT
- OTHER STANDARDS JB/T11967 EN378-2
- THE INLET AND OUTLET PIPES ARE COPPER PIPES

**PRODUCT PARAMETERS**

TUBE NUMBER	49
TUBE TYPE	25.4*2- 20
TUBE MATERIAL (LONG USING LIFE ALLOY)	LLA9153(3F03)+Zn- H112
MANIFOLD TYPE	φ38
FIN TYPE	LOUVERED 25.4*0.08 FPI 23
FIN MATERIAL	AA4343/3003/4343
PASS	35/14



UNMARKED TOLERANCE	DESCRIPTION:									
	Microchannel heat exchanger									
<table border="1"> <tr> <td>X</td> <td>±1.5</td> </tr> <tr> <td>X.X</td> <td>±1</td> </tr> <tr> <td>X.XX</td> <td>±0.5</td> </tr> <tr> <td>/</td> <td>±1°</td> </tr> </table>	X	±1.5	X.X	±1	X.XX	±0.5	/	±1°	MODEL:	REV.
	X	±1.5								
X.X	±1									
X.XX	±0.5									
/	±1°									
	RC-1500-S	A								
VIEW	CODE:	CREAT:								
	021U0095R	AUDIT:								
APPROVED BY CUSTOMER SIGNATURE:	PROCESS:									
	APPROVE:									